CE	MED	·ΛΙ

GENERAL				
Front Interface	HDMI x1, USB C x1, USB A 3.0 x2, USB B 3.0 x1, MIC In x1			
Rear Interface	USB A x3, USB C x1, USB B x3, HDMI In x2, DisplayPort x1, OPS Slot x1, RS232 x1, Audio Out x1, Line out or Headphone x1, SPDIF x1, HDMI Out x1, Line out or Headphone x1, SPDIF x1, HDMI Out x1, LAN 1000Base-T x2			
re-installed app	Whiteboard, Picture-In-Picture, Eshare, Browser, Settings, Google Play Store, Google Calender, Files by Google, Search, Chrome, Gmail, Ma YouTube, Drive, YT Music, Google TV, Meet, Photos			
Dimensions: W x D x H (mm)	1,513 x 93 x 953	1,735 x 92 x 1,077	1,981 x 92 x 1,217	
ackage size: W x D x H (mm)	1,630 x 185 x 1,057	1,859 x 227 x 1,190	2,119 x 225 x 1,320	
/eight (kg)	40	52	65	
lousing material (face frame/		Aluminium/metal plate		
ack shell)		Black/black		
lousing colour (face frame/back hell)		BIACK/DIACK		
ESA	4-M8 screw hole 600 x 400 mm	4-M8 screw hole 800 x 400 mm	4-M8 screw hole 800 x 400 mm	
DISPLAY PANEL				
land size, diagonal	CEII wide	75"	86" wide	
Panel size: diagonal	65" wide 1,428 x 803	75" wide 1,650 x 928		
Effective area: W x H (mm) Resolution: maximum (Full HD)	1,420 X 003	3,840 x 2,160	1,895 x 1,065	
, ,				
Colours: maximum		1,070,000,000		
Brightness: maximum (cd/m²)		400		
Contrast ratio	5,000 : 1	5,500 : 1	4,000 : 1	
Pixel pitch (mm)	0.124 x 0.372	0.14325 x 0.42975	0.4935 x 0.4935	
Response: grey to grey (ms)	6.5	6.5	8	
Refreshing frequency		60 Hz		
/iewing angle: H/V (°)		178/178		
.ED lifetime		50,000 hours		
OUCH SYSTEM				
ouch technology	Infrared Touch Frame/Zero Bonding			
Accuracy (mm in touchable area)		1		
/lulti touch	Win11/10/8/7/XP, Android			
Single touch	Linux, Mac OS X, Chrome			
Protection glass thickness:		3.2		
ncluding AR coating (mm)				
Maximum touch points		40		
Coating	Anti-glare, Anti-fingerprint			
Hardness		8 H		
ECOLOGY				
Power consumption: standard mode (W)		< 200		
Power consumption: eco mode	< 133	< 150	< 168	
W) Power consumption: standby		< 0.5		
node (W)				
Power consumption: with OPS (W)	< 380	< 420	< 520	
perating temperature (°C)		0 - 40		
Operating humidity (%)		20 - 80		
Ititude limitation: sea level (m)		Lower than 5,000		
Maximum daily operation hours	Do not use the machine continuously/intermittently for more than 18 hours per day. Failure to do so could result in malfunction.			
exclude stand-by time)				
Storage temperature	-10°C ~ +50°C			
Storage humidity	15% ~ 80% RH Non-Condensing			
CONTROLLER/ELECTRICAL				
os	Android 13.0 EDLA			
Audio output power	15 W x2			
RAM	8 GB			
	128 GB			
ROM Storage		120 GD		
ROM Storage VIFI		Wifi5 Module, Wifi6 Module		

A6510 A7510 A8610

## **ACCESSORIES**

Power cable
Touch pen x2
Read this first sheet
Quick guide sheet
Batteries AAAx2
Remote control
USB type C cable (2m)
HDMI 2.0 cable (3m)
USB A.B 3.0cable (3m)
Plastic clamp(3pcs+3pcs)

For availability of models, options and software, please consult your local supplier.



