

B & W printers/multifunctional products

M 320SE
M 320FSE
P 311SE

RICOH
imagine. change.



M 320SE / M 320FSE / P311SE series specifications

The M 320SE / M 320FSE / P 311SE series provides the right solution for your needs, whether you're looking for straightforward, compact printing or efficient multifunction capabilities. Designed for high productivity with minimal maintenance, these printers are ideal for busy environments. Their compact footprint makes them perfect for smaller spaces, and their intuitive operation ensures easy management and upkeep.

Features for printers in this series include:

- Up to 32 pages per minute output
- M 320SE: compact footprint, ideal for smaller spaces
- M 320FSE: intuitive 4.3 inch touch panel to easily switch between print, copy, scan and fax modes
- P 311SE: straightforward to use and manage and highly durable with a toner cartridge that can last up to a year
- SNMPv3-encrypted communications for device monitoring, secure email transmissions by SMTP over SSL/TLS

M 320SE/M 320FSE/P 311SE

MAIN SPECIFICATIONS

	M 320SE	M 320FSE	P 311SE
GENERAL			
Warm-up time	30 seconds	30 seconds	26 seconds
First copy speed: BW		7.1 seconds	
Continuous output speed		32 ppm	
Memory: standard	256 MB	256 MB	128 MB
Weight	18 kg	18 kg	13 kg
Dimensions: W x D x H	405 x 392 x 407 mm	405 x 392 x 420 mm	370 x 392 x 262 mm
Power source		220 - 240 V, 50 - 60 Hz	
Laser classification	Class 1 Laser Product (IEC60825 - 1:2014)		
COPIER (M 320SE, M 320FSE)			
Multiple copying	Up to 99 copies	Up to 99 copies	-
Resolution	1,200 x 1,200 dpi	1,200 x 1,200 dpi	-
Zoom	From 25% to 400% in 1% steps	From 25% to 400% in 1% steps	-
PRINTER			
Printer language: standard	PCL5e (MAC), PCL6 (Windows & Linux), PostScript3 (Windows)		
Print resolution: maximum	1,200 x 1,200 dpi		
Network interface: standard	Ethernet 10 base-T/100 base-TX, USB2.0 Type B		
Windows® environments	Windows® 8.1, Windows® 10, Windows® Server 2012, Windows® Server 2012R2, Windows® Server 2016, Windows® Server 2019		
Mac OS environments	Macintosh OS X v10.10 or later		
Other supported environments	Linux environment		
SCANNER (M 320SE, M 320FSE)			
Scanning: B/W	13 ipm	13 ipm	-
Scanning: full colour	4.5 ipm	4.5 ipm	-
Resolution: maximum	600 dpi	600 dpi	-
FAX (M 320FSE)			
Compatibility	-	ITU-T (CCITT) G3	-
Transmission speed	-	3 seconds	-
Modem speed: maximum	-	33.6 Kbps	-
PAPER HANDLING			
Recommended paper size	Standard paper tray(s) A4, A5, A6, B5, B6		
Paper input: standard	300 sheets		
Paper input: maximum	550 sheets		
Paper output: standard	50 sheets	50 sheets	125 sheets
Paper weight	52 - 162 g/m²		
ECOLOGY			
Power consumption: operation	514 W	520 W	512 W
Power consumption: sleep	0.87 W	0.87 W	0.72 W
TEC*	0.423 kWh/week	0.423 kWh/week	0.408 kWh/week
INPUT/OUTPUT TRAYS AND FINISHER OPTIONS			
1x 250-sheet paper tray			
CONSUMABLES			
Starter toner	1,000 prints	7,000 prints	7,000 prints
Toner (regular yield)	-	3,500 prints	-
Toner (high yield)		7,000 prints	
Consumable yield measuring method ISO/IEC 19752			



ISO9001 certified, ISO14001 certified, ISO27001 certified

COMMISSION REGULATION (EU) 2019/2020. The light source of this product is not intended for applications other than image printing.

Ricoh Europe (Netherlands) B.V.

John M. Keynesplein 10-B
1066 EP Amsterdam
The Netherlands



+31 (0)20 5774111



ricoh-europe.com

RICOH
imagine. change.

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The images in this brochure are not real photographs and slight differences in detail might appear, including in relation to colour. Not all services and solutions are available to all customers. Copyright © 2025 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.